

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
10 May 2001 (10.05.2001)

PCT

(10) International Publication Number  
WO 01/33216 A1

(51) International Patent Classification<sup>7</sup>: G01N 33/487,  
33/543, 27/42

(21) International Application Number: PCT/US00/29540

(22) International Filing Date: 27 October 2000 (27.10.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
09/434,026 4 November 1999 (04.11.1999) US

(71) Applicant: THERASENSE, INC. [US/US]; 1360 South  
Loop Road, Alameda, CA 94502 (US).

(72) Inventors: LIAMOS, Charles, T.; 2444 Via De Los  
Milagros, Pleasanton, CA 94566 (US). FELDMAN,


Benjamin, J.; 5830 Colby Street, Oakland, CA 94618 (US). FUNDERBURK, Jeffery, V.; 37670 Carriage Circle Common, Fremont, CA 94536 (US). KRISHNAN, Rajesh; 4211 Central Avenue, Apt. #1, Fremont, CA 94536 (US). PLANTE, Phillip, J.; 268 Monterey Boulevard, San Francisco, CA 94131 (US). VIVOLO, Joseph, A.; 1548 Haight Street, San Francisco, CA 94117 (US). JIN, Robert, Y.; 7663 Pineville Circle, Castro Valley, CA 94552 (US). CLOUD, Michael, S.; 2008 Pacific Avenue #C, Alameda, CA 95401 (US). COLMAN, Fredric, C.; 13864 Campus Drive, Oakland, CA 94605 (US).

(74) Agent: DAIGNAULT, Ronald, A.; Merchant & Gould P.C., P.O. Box 2903, Minneapolis, MN 55402-0903 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model),

[Continued on next page]

(54) Title: SMALL VOLUME *IN VITRO* ANALYTE SENSOR AND RELATED METHODS



(57) Abstract: A small volume sensor, and methods of making, for determining the concentration of an analyte, such as glucose or lactate, in a biological fluid, such as blood or serum, using techniques such as coulometry, amperometry, and potentiometry. The sensor includes a working electrode and a counter electrode, and can include an insertion monitoring trace to determine correct positioning of the sensor in a connector. In one embodiment, the sensor determines the concentration of the analyte by discharging an amount of charge into the sample, determining the time needed to discharge the charge, and determining the current used to electrolyze a portion of the analyte using the amount of charge and the amount of time.

WO 01/33216 A1